

J493

## SUPER 90 FLOOR FINISH

### FAST DRYING, HIGH GLOSS, MULTI-COATABLE

This product is an excellent all-purpose floor finish designed to provide a brilliant finish without buffing. Special polymers, polyethylenes and resins provide an incredibly durable film designed for no-buff and spray-buff systems. This is a hard scuff resistant finish that will not show heel marks or soiling.

Total Activity	21%
Floor Solids	18%
Specific Gravity	1.03

It dries in about 20 minutes and can be buffed with a high speed machine to further enhance the gloss. This no-buff system is ideal for areas where use of a floor machine is not practical. The finish is maintained by dust mopping and damp mopping. When the surface shows signs of wear, a thorough cleaning will prepare it for re-coating. The worn area can be touched up with an additional coat of finish to restore the gloss. Careful feathering can eliminate the need to coat the entire area.

This system will require periodic stripping to renew the floor. Use a good speed stripper to ensure complete removal of old finish.

**SPRAY BUFF SYSTEM:** Spray buffing will clean and remove marks, repairs and improve the gloss. It is important to have a good base finish to work with. The idea of spray buffing is to maintain the finish, remove the light soil and polish the floor all in one step.

**DIRECTIONS:** Use only clean equipment (applicator, mops, and pails), in applying the finish. Apply thin, even coat. Do not rub! Another thin coat is recommended for added gloss and protection. One litre covers 60-65 square meters. Allow 20 minutes for drying before applying a second coat. The use of a sealer is required on new floors and newly stripped floors before applying finish. This is especially important for porous floors.

**FOR COMMERCIAL USE**

2016-11-29



Intertek