

J844

TECHNICAL DATA SHEET

FABRIC PROTECTOR

This product is a sophisticated combination of chemicals with a fluoroethylene polymer base designed to form an invisible antistatic shield. It will keep dirt, dust and grime from clinging to fabric fibres and keep wet soil from penetrating. Vacuuming will remove more soil from treated carpets and other fabrics and prevent dirt from becoming imbedded under the surface where it does the most damage.

Fabric Protector may be used on carpet, upholstery and drapes. Its effectiveness will vary with type of fabric. Each type of fabric must be pre-tested. This is particularly advisable for use on interior fabrics of automobiles where different types of dyes are used.

DIRECTIONS: Uniformly spray product with a fine spray on clean carpet or upholstery using a spray tank or trigger sprayer. It may be applied to either damp or dry fabric. For damp fabrics, dilute 1 part product with 1 part water. For dry fabrics, dilute 1 part product with 4 parts water. In either case, 1 litre of product should cover an area of approximately 23 square meters or 250 square feet.

Brush the fabric lightly and set the nap with a soft bristle brush or a sponge slightly dampened with Fabric Protector. Allow the fabric to dry before use. To enhance the appearance of some fabrics it may be desirable to brush and vacuum after drying.

COMMERCIAL USE ONLY

2016-12-6

**Intertek**