

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION

OSTREM CHEMICAL CO. LTD.
2310 - 80 AVENUE
EDMONTON AB T6P 1N2

Phone: 780-440-1911 or 780-446-0177
In Case of Emergency Only:
phone CANUTEC at (613) 996-6666

Product name: SHIPPING WAX REMOVER

Code: A295

Other name:

Distributed by:

Product use: degreaser

Date completed: April 01, 2014

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	%W/W	CAS number
kerosene	7-13	8008-20-6
propylene glycol	3-7	57-55-6
non-ionic surfactant blend	15-40	not avail.

3. HAZARDS IDENTIFICATION

Combustible liquid. Eye irritant. Harmful if swallowed.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion:

Induce vomiting only on the direct advice of a poison control centre. Get medical attention.

Eye contact: Flush with plenty of water for at least 15 minutes. Get medical attention.

Skin contact: Remove contaminated clothing and flush with plenty of water.

5. FIRE - FIGHTING MEASURES

Flash point (test method): 46C

Flammable limits (%): Not available

Lower: Not available

Upper: Not available

Fire extinguishing substances: dry chemical, carbon dioxide, water spray (fog) or foam

Autoignition temperatures: Not available

Hazardous combustion products: May liberate carbon monoxide, carbon dioxide, nitrogen oxides and sulphur oxides.

Explosion data:

Sensitivity to mechanical impact: Not available

Sensitivity to static discharge: Not available

Special firefighting procedures: As for surrounding fire. Fire fighters should wear full protective clothing and self contained breathing equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Wear appropriate protective equipment.

Environmental precautions: Prevent from entering sewers, waterways or low areas.

Methods for cleaning up: Isolate hazard area and restrict access. Small spills: soak up with inert absorbent material and scoop into containers. Large spills: prevent contamination of waterways. Dike and pump into suitable containers. Clean up residual with absorbent material, place in appropriate container and flush with water.

7. HANDLING AND STORAGE

Handling: Do not ingest. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
Storage: Store in a cool, dry area. Keep container tightly closed. Store in a segregated and approved area. Ensure storage containers are grounded/bonded.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: Provide exhaust ventilation to keep airborne levels below recommended exposure limits.
Respiratory protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH approved respirator
Eye protection: Chemical goggles. Wear a face shield if splashing hazards exists.
Other protection: Wear protective clothing as necessary to prevent skin contact.

Exposure limits:

INGREDIENT	ACGIH	OSHA	Other
kerosene	200 mg/m ³		

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid	Solubility in water: insoluble
Boiling point: Not available	Vapour pressure: Not available
Vapour density: Not available	Evaporation rate: Not available
Freezing point: Not available	Odour threshold: Not available
Sp. Gravity: 0.988	pH: 7.5
Appearance & odour: clear liquid with raspberry / solvent odour	

10. STABILITY AND REACTIVITY

Stability: Stable
Conditions of instability: Not available
Incompatibility: () Water (X) Oxidizers (X) Acid () Base () Other
Conditions of reactivity: Not available
Hazardous decomposition products: Not available

11. TOXICOLOGICAL PROPERTIES

POTENTIAL ACUTE HEALTH EFFECTS

Inhalation: Irritating to respiratory system.
Ingestion: Harmful if swallowed.
Eye contact: May cause mild to severe irritation such as stinging, tearing, redness and swelling of the eyes.
Skin contact: May cause skin irritation.
Skin absorption: Not applicable

POTENTIAL CHRONIC HEALTH EFFECTS:

Inhalation: No known significant effects.
Ingestion: Not available
Eye contact: Not available
Skin contact: Not available
Skin absorption: Not available
Prolonged overexposure to high concentrations of ethylene glycol monobutyl ether by absorption, ingestion and inhalation has caused blood, liver and kidney effects in laboratory animals.

Irritancy of product: see WHMIS criteria

Sensitization of product: Not available
Carcinogenicity: IARC (1, 2A or 2B) No known significant effects.
ACGIH: (A1, A2 or A3) No known significant effects.
Reproductive toxicity: No known significant effects.
Teratogenicity: No known significant effects.
Mutagenicity: No known significant effects.
Synergistic product: Not available

HAZARDOUS INGREDIENTS
kerosene

CAS NO. TOXICITY DATA
8008-20-6 LD₅₀ Oral (rat) 5000 mg/kg
LD₅₀ Dermal (rabbit) 3000 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicological information: Not available
Other information:

13. DISPOSAL CONSIDERATIONS

Waste disposal: Disposal of all waste must be done according to local, provincial and federal regulations.

14. TRANSPORT INFORMATION

TDG classification: In amounts over 450 L: FLAMMABLE LIQUID N.O.S. (PETROLEUM DISTILLATES), Class 3; UN 1993; PG III
Not regulated in amounts less than 450 L.

15. REGULATORY INFORMATION

WHMIS: B3 Combustible Liquid
D2B Toxic Material Causing Other Effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. PREPARATION INFORMATION

Prepared by: Technical Services Department, Ostrem Chemical Co. Ltd., Ph: (780) 440-1911