

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION

OSTREM CHEMICAL CO. LTD.
2310 - 80 AVENUE
EDMONTON AB T6P 1N2

Phone: 780-440-1911 or 780-446-0177
In Case of Emergency Only:
phone CANUTEC at (613) 996-6666

Product name: RAGE SPEED STRIPPER

Code: J459

Other name:

Distributed by:

Product use: floor stripper

Date completed: November 23, 2015

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	%W/W	CAS number
Potassium hydroxide (45%)	3-7	1310-58-3
Ethylene glycol monobutyl ether	1-2	111-76-2
Monoethanolamine	7-13	141-43-5

3. HAZARDS IDENTIFICATION

Corrosive liquid. Causes burns. Harmful if swallowed.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Induce vomiting only on the direct advice of a poison control centre. Drink 1-2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

Eye contact: Flush with plenty of water for at least 15 minutes. Get medical attention.

Skin contact: Remove contaminated clothing and flush with plenty of water.

5. FIRE - FIGHTING MEASURES

Flash point (test method): Not applicable

Flammable limits (%): Non-flammable

Lower: Not applicable

Upper: Not applicable

Fire extinguishing substances: Use extinguishing media appropriate for surrounding fire.

Autoignition temperatures: Not applicable

Hazardous combustion products: May liberate carbon monoxide, carbon dioxide and oxides of sodium.

Explosion data:

Sensitivity to mechanical impact: Not applicable

Sensitivity to static discharge: Not applicable

Special firefighting procedures: As for surrounding fire. Fire fighters should wear full protective clothing and self contained breathing equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Wear appropriate protective equipment.

Environmental precautions: Prevent from entering sewers, waterways or low areas.

Methods for cleaning up: Isolate hazard area and restrict access. Small spills: soak up with inert absorbent material and scoop into containers. Large spills: prevent contamination of waterways. Dike and pump into suitable containers. Clean up residual with absorbent material, place in appropriate container and flush with water.

7. HANDLING AND STORAGE

Handling: Do not ingest. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
Storage: Keep out of reach of children. Keep container tightly closed. Store in a cool, dry area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: Provide exhaust ventilation to keep airborne levels below recommended exposure limits.
Respiratory protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH approved respirator
Eye protection: Chemical goggles. Wear a face shield if splashing hazards exists.
Other protection: Wear protective clothing as necessary to prevent skin contact.

Exposure limits:

INGREDIENT	ACGIH	OSHA	Other
Potassium hydroxide (45%)	2 mg/m3 Ceil.	Not available	
Ethylene glycol monobutyl ether	20 ppm TWA	Not available	
Monoethanolamine	TLV TWA: 3 ppm 8 hours TLV STEL: 6 ppm 15 minutes		

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid	Solubility in water: Complete
Boiling point: 100C	Vapour pressure: Not available
Vapour density: Not available	Evaporation rate: Not available
Freezing point: Not available	Odour threshold: Not available
Sp. Gravity: 1.0385	pH: 13.8; 1% solution: 11.4
Appearance & odour:	yellow liquid with pine/lemon scent

10. STABILITY AND REACTIVITY

Stability: Stable
Conditions of instability: Not available
Incompatibility: () Water (X) Oxidizers (X) Acid () Base () Other
Conditions of reactivity: Reacts with acids and metals
Hazardous decomposition products: Not available

11. TOXICOLOGICAL PROPERTIES

POTENTIAL ACUTE HEALTH EFFECTS

Inhalation: Corrosive to respiratory system.
Ingestion: Harmful if swallowed. Causes burns to mouth, throat and stomach.
Eye contact: Causes burns
Skin contact: Causes burns
Skin absorption: Not available

POTENTIAL CHRONIC HEALTH EFFECTS:

Inhalation: Repeat or prolonged exposure may cause damage to lungs.
Ingestion: Not available
Eye contact: Not available
Skin contact: Not available
Skin absorption: Not available
Prolonged overexposure to high concentrations of ethylene glycol monobutyl ether by absorption, ingestion and inhalation has caused blood, liver and kidney effects in laboratory animals.

Irritancy of product: See WHMIS criteria
Sensitization of product: Not available

Carcinogenicity: IARC (1, 2A or 2B)
ACGIH: (A1, A2 or A3)
Reproductive toxicity:
Teratogenicity:
Mutagenicity:
Synergistic product:

No known significant effects.
No known significant effects.
No known significant effects.
No known significant effects.
No known significant effects.
Not available

HAZARDOUS INGREDIENTS	CAS NO.	TOXICITY DATA
Potassium hydroxide (45%)	1310-58-3	LD ₅₀ Oral (rat) 273 mg/kg
Ethylene glycol monobutyl ether	111-76-2	LD ₅₀ Oral (rat) 1480 mg/kg LD ₅₀ Dermal(rabbit) 630 mg/kg
Monoethanolamine	141-43-5	LD ₅₀ Oral (rat) 1090 mg/kg LD ₅₀ Dermal (rabbit) 1000 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicological information: Not available
Other information:

13. DISPOSAL CONSIDERATIONS

Waste disposal: Disposal of all waste must be done according to local, provincial and federal regulations.

14. TRANSPORT INFORMATION

TDG classification: POTASSIUM HYDROXIDE, SOLUTION; UN 1814; Class 8; PG II

15. REGULATORY INFORMATION

WHMIS: E Corrosive material
D2B Other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. PREPARATION INFORMATION

Prepared by: Technical Services Department, Ostrem Chemical Co. Ltd., Ph: (780) 440-1911