

B269

TECHNICAL DATA SHEET

**AUTOWASH 2
(ALKALI)**

AUTOWASH 2 (Alkali) is designed to be used in conjunction with an acid cleaner, **AUTOWASH 1 (Acid)**, in a cold or hot water pressure spray cleaning system. Once road film and soil have been loosened from the truck's surface by AUTOWASH 1, AUTOWASH 2 will completely remove these soils from the surface. In addition to working synergistically with AUTOWASH 1, it will neutralize the acid cleaner to deter any corrosion that might otherwise occur. AUTOWASH 2 can also be used alone as a high alkaline, free rinsing pressure wash detergent.

AUTOWASH 2, when used in conjunction with AUTOWASH 1 emulsifies, neutralizes and quickly loosens dirt, grime and oily residue on all vehicles. Use in high or low pressure cleaning systems.

The dilution of AUTOWASH 2 will depend on the equipment used, the pressure available, water conditions and temperature. On average, the recommended dilution is 1/2 to 1 oz per gallon (3 to 6 ml per liter).

When washing vehicles with a two-phase system, use AUTOWASH 2 immediately following application of AUTOWASH 1. It should be applied in the same pattern as AUTOWASH 1 to allow the cleaners to have equal contact time.

COMMERCIAL USE ONLY

October 18, 2016

**Intertek**